



FS1500 Series Open-Voice QwikBUS Intercom Stations

S.T.R. FS1500 QwikBUS Series stations are designed to work as an apartment type open-voice intercom station, using a minimal of wiring. All FS1500 stations in a building can be wired on only two (2) twisted common (loop) wires. The QwikBUS system can support hundreds of FS1500 stations on a single system. Choose from White and five (5) other decorator inspired finishes.

These attractive and trim stations easily surface mount right on the finished wall, or can flush mount over a model UMF1000 flush plastic housing with model HWB mounting screws. Stations can be changed to desk mount with the addition of a model TZ-FS (White) desk adapter.

All FS1500 series QwikBUS stations selectable electronic tone signalling, Voice On, Door Release, Call Volume, one (1) momentary button switches. These switches can be used for door release, or other signalling functions, depending upon system configuration. All FS1500 series have two (2) selective calling buttons, marked '1' and '2' which allow internal calling (and inter-communication) within up to three (3) FS1500 stations within a single apartment or suite location.

FEATURES

- Crystal-Clear Half-Duplex Voice Operation
- Easy Installation - Only 2 Common (loop) Wires Required
- Eavesdrop Privacy - Inter-Communication capable
- Clear Voice Fidelity using Electret Condenser Microphones
- Rugged and Reliable / Simple to Operate
- Mounts Surface, or optionally Flush or Desk mount (with optional extra cost adapters)
- Available in White and five (5) other decorator finishes

SPECIFICATIONS

Dimensions:	All FS1500 series stations are 3.35"W (86mm) x 5.55"H (141mm) x 0.87"D (23mm). All dimensions shown are for the surface wall type station.
--------------------	--



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The 2-Wire open voice intercom station(s) S.T.R. QwikBUS FS1500 in (White, Titanium, 24K Gold Plated, Crystal Glass, Stainless Steel or Anthracite) colour. Station(s) shall be mounted (surface, flush or desktop), with required optional mounting components. Station(s) shall feature electret condenser microphone for exceptional half duplex voice fidelity (requiring no pressing of Talk or Listen buttons).

Stations that include simplex type or other voice technologies shall not be acceptable. Station shall include a Voice On, Door Release, Call Volume and two (2) internal calling buttons for inter-communication in a single apartment/suite. Station(s) shall include a built-in (user selectable) electronic call tone signal. Station(s) shall require only two (2) common (loop) wires for system operation, or can be intermixed with QwikBUS video-intercom systems, using the optional FSAMV adapter board. Contractor shall observe all local and national electrical and building codes.